





C230 2EBIE2

sized chore or task.

PERFORMANCE AND UNMATCHED EFFICIEUCY EXPERIENCE UNPARALLELED COMFORT, MAXIMUM

ensures sufficient power and torque for anydisplacement over previous KIOTI models, it fuel consumption. With a 22% increase in torque, the highest in its class, while minimizing delivers 24.5 horsepower and exceptional The KIOTI 1.2L 3CYL water-cooled diesel engine

Fuel Efficient Diesel Engine



Mid and Rear PTO

ensuring uninterrupted productivity. simultaneously reducing downtime to change implements Operate the rear and mid PTO's independently or




Improved Lever Layout and Operability

comfortable and efficient. ensure precision and confidence, making your work more design for a natural fit and intuitive operation. Our levers Enjoy improved control and comfort with an ergonomic



Factory Installed Cab

push-pull lever, ensuring quick and effortless control over traction and stability, and is easily engaged with a simple Four-wheel drive comes standard, providing enhanced









Twin HST Pedals

Twin HST pedals enable easy forward and reverse movement, with smooth acceleration and deceleration. The dual pedals simplify operation, reducing operator fatigue during long hours of work and repetitive tasks.



Power with Tilt Steering

Minimizes the effort required to make tight, repetitive turns. The steering wheel tilts with the simple push of a lever, allowing easy adjustment to fit the operator's needs.



Illuminated Digital Instrument Panel

The instrument panel provides critical information at a glance, including PTO engagement, vehicle information, fuel level, notifications, and alerts.



Projection Head and Working Lamps

The LED projection head and working lamps pierce the darkness, casting a wide, clear beam that illuminates your field for safe, precise maneuvering even after sunset.



Integrated Multimedia Display (Optional)

Elevate your entertainment with our multimedia display, boasting vivid audio/video and superior sound quality. Pair it with a separately purchased high-quality camera for an immersive experience, enhanced by a seamless AV multimedia deck for top-tier performance and connectivity.



Rear View Camera (Optional)

Revolutionize your workday with the rear view camera, eliminating blind spots and enhancing convenience and precision. With a clear, real-time view, operators can confidently perform three-point maneuvers and reverse with ease.



BUILT WITH COMFORT IN MIND C230 2EBIE2





for efficiency and durability, this system enhances operator

cooling, ensuring a comfortable cabin year-round. Enjoy

reliable cooling in summer and warmth in winter. Engineered

Our advanced HVAC system provides optimized heating and





smooth ride.

the joystick, allowing you to accomplish more in less time.



traction in slippery conditions like uneven or muddy terrain. The lever easily engages the differential, ensuring optimal

Rear Differential Lock



towards the rear of the tractor, facilitating in-cab operation of

The swivel feature allows the operator to rotate the seat

Swivel Seat for Backhoe Operation (Optional)

the backhoe when installed.

Designed for ease of use, this feature allows for precise and



minimizing the impact of rough surfaces and ensuring a

The Deluxe Suspension Seat is engineered to deliver

comfort for the operator by absorbing shocks and vibrations,

responsive control of the hydraulic thumb directly through

vantage point stays clean and uncompromised. wiper) keeps your view crystal clear, battling both rain and Standard front double arm wiper (optional rear single arm

with minimal effort. eliminating side insertion and getting you to work faster driving over it. This innovative design streamlines setup, allowing you to easily mount the mid mower by simply Offers a seamless and efficient mounting experience, Drive-Over Deck

work, reducing fatigue and ensuring a uniform finish.

Cruise Control

simply set your desired speed and let the tractor do the $% \left(1\right) =\left\{ 1\right\} =\left$

cruise control. Perfect for tasks like mowing or spraying,

Maintain consistent speeds effortlessly with the integrated

comfort and productivity.

0

贷

dust. Their optimized placement ensures the operator's Front and Rear Wipers









KIOTI Connect Capable

KIOTI Connect is an intuitive app that provides real-time insights, maintenance tracking, and remote diagnostics, keeping you connected to your machine like never before.



USB Charging Port with AUX / Stereo

Stay connected and entertained with the built-in USB charging port and AUX/stereo system. Connect your phone to the cabin speakers via AUX, or upgrade to optional Bluetooth stereo or audio den for enhanced music and streaming capabilities.



Rubber Floor Mats

Rubber floor mats are designed to protect the base of your tractor from dents and scratches, ensuring long-lasting durability. Additionally, these mats are easy to clean, allowing for quick removal of dirt and debris.



Class-Leading Torque

Boasting an impressive 51.63 lb.-ft of torque, it is the highest-torque tractor in its class. This exceptional power output is provided by its robust 1.2L KIOTI diesel engine, which produces 24.5 horsepower. Tackle tasks with ease, from mowing and tilling to landscaping and hauling.



Standard Quick Attach

The Quick Attach feature makes switching tasks easy, with minimal effort and maximum convenience. Left and right levers allow you to effortlessly install and remove attachments from the loader quickly & efficiently.



Self-Leveling Loader (Optional)

Maintains the desired bucket angle when lifting and lowering, preventing the need to manually position the bucket throughout the lift/lower cycle to keep your material in the bucket. This can increase productivity while adding a layer of safety to your worksite.



In-Cab Loader Attachment Access

Enjoy the convenience and safety of managing the loader quick release from the comfort of the cab, eliminating the need to repeatedly get on and off the tractor.



Backhoe Compatible Cabin

Allows for smooth transitions between driving and digging, with a removable rear glass and back panel, quickly transition from tractor to backhoe operations for instant access to controls. This design minimizes downtime and maximizes productivity.



ATTACHMENTS

BACKHOE SPECIFICATIONS

MODEL		SB2530
Bucket Sizes	in. (mm)	8 (203.2) 12 (304.8) 16 (406.4)
Digging Depth (Two Foot Flat Bottom)	in. (mm)	72.4 (1,840)
Reach from Center Line of Swing Pivot	in. (mm)	105 (2,668)
Loading Height (Bucket at 60°)	in. (mm)	59.4 (1,510)
Maximum Leveling Angle	deg.	8
Swing Arc	deg.	150
Transport Height (Maximum)	in. (mm)	68.5 (1,739)
Transport Overhang	in. (mm)	41.3 (1,050)
Bucket Rotation	deg.	165
Stabilizer Spread (Down Position)	in. (mm)	78 (1,981)
Stabilizer Spread (Up Position)	in. (mm)	54 (1,372)
Angle of Departure	deg.	17
Shipping Weight (Without Bucket)	lbs. (Kgf)	613 (278)
Bucket Digging Force	lbs. (Kgf)	2,105 (955)
Dipperstick Digging Force	lbs. (Kgf)	1,184 (537)
Operating Pressure	psi (bar)	1,886 (130)

FRONT END LOADER SPECIFICATIONS

MODEL		SL2530 (Non-Self Leveling)	SL2530 (Self Leveling*)
Maximum Lift Height (to Pivot Point)	in. (mm)	70.9 (1,800)	71.1 (1,807)
Clearance w/Bucket Dumped (@ 45°)	in. (mm)	50.4 (1,280.2)	51.6 (1,310)
Reach at Maximum Height	in. (mm)	28.3 (718)	27.4 (695)
Reach w/Bucket on Ground	in. (mm)	54.2 (1,377)	54.4 (1,382)
Maximum Rollback Angle	deg.	27	42
Diggiging Depth Below Grade	in. (mm)	8.1 (205)	7.5 (190)
Overal Height (in Carry Position)	in. (mm)	43.4 (875)	37.4 (905)
Depth of Bucket (to Back of Inner Shell)	in. (mm)	17 (432)	17 (432)
Height of Bucket	in. (mm)	18.6 (473)	18.6 (473)
Length of Bucket (to Pivot Pin)	in. (mm)	22 (559)	22 (559)
Lift Capacity to Full Height (at Pivot Pins)	lbs. (kg)	871 (395)	913 (414)
Breakout Force (at Pivot Pins)	lbs. (kg)	1,299 (589)	1,281 (581)
Relief Setting (Loader Control Valve)	psi (Kgf)	1,849 ~ 1,920 (130 ~ 135)	1,849 ~ 1,920 (130 ~ 135)
Bucket Size (QA)	in. (mm)	48 (1219.2)	48 (1219.2)
Bucket Capacity (Heaped)	ft.3 (m3)	6.70 (0.19)	6.70 (0.19)
Anchonical colf lavaling (antional)			

^{*}Mechanical self leveling (optional).

MID-MOUNT MOWER SPECIFICATIONS

MODEL		SM2554	SM2560
Mounting Method		Suspended Linkage	Suspended Linkage
Adjustment of Cutting Height		7 Step (0.5"/ Step)	7 Step (0.5"/ Step)
Cutting Width	in. (mm)	54 (1,368)	60 (1,524)
Cutting Height	in. (mm)	1 - 4 (25.4 - 101.6)	1 - 4 (25.4 - 101.6)
Weight	lbs. (kg)	249 (113)	254.0 (115.2)
Deck Thickness	in. (mm)	0.1 (3.2)	0.1 (3.2)
Blade Spindle Speed	rpm	2,805	2,805
Blade Tip Velocity	m/s	69.2	75.2
Blade Length	in. (mm)	18.5 (470)	20.4 (517)
Number of Blades		3	3
Total Length	in. (mm)	35.7 (908)	37.9 (962)
Total Width	in. (mm)	69.3 (1,760)	73.4 (1,865)
Total Height	in. (mm)	10.5 (267)	10.7 (273)
Auto Connector Link KIT	in. (mm)	N/A	Opt
Auto Joint KIT	in. (mm)	N/A	Opt

^{*} Specifications and design are subject to change without notice.

LIT-CS30C-01

Toll free 877-GO-KIOTI Fax 919-374-5001 6300 KIOTI Drive, Wendell, NC 27591 USA

Dealer Imprint Area

© 24" aft of hitch.	NOTE: Specifications and design are subject to change without no
Wheelbase	(mm 42.99£,t).ni 01.33
JugieH Illerayo	(mm 40.890,2).ni 03.28
Overal Width (min. tread)	(mm S8.3SS,t) .ni 0E.84
Overall Length w/o front weight & w/ 3-pt hitch	(mm 07.£t3,2).ni 0e.20t
DIWENSIONS	
Вечегае	0 ~ 6.15 mph (0 ~ 9.90 kph)
Forward	(dq4 74.4t ~ 0) dqm ee.8 ~ 0
TRAVEL SPEED	
Rear AG.	26 × 12 - 12
Front AG.	01- 3.8 x 81
Fire Size	
No. of Standard Remote Valves (Rear)	(IsnoitqO) t
Hydraulic Lift Control System	Mechanical
Maximum Lifting Capacity*	700 lbs. (317.52 kg)
3-Point Hitch	Category I
Pump Capacity (max flow rate)	Steering 2.03 GPM (7.7) MqD 4.9 GPM (18.7 lpm)
dwnd	Open Center
HYDRAULIC SYSTEM	
4WD Type	Mechanical
Rear PTO	240
PTO	Electric / Hydraulic
Вгаке	osiO JeW
Differential Lock	Rear Standard
Speeds	Infinite
Transmission	2 Range Hydrostatic
DRIVE TRAIN	
Fuel Tank Capacity	6.6 gal. (25.5 ^g)
Rated Revolution	mq1 000,£
Displacement	(30 SE2.\f) .ni.n 4\subseteq .17.237
PTO	19.30 HP (14.32 kW)
Engine Gross	24.50 HP (18.27 kW)
Σλbe	KIOTI 3 Cylinder, Water-Cooled Diesel
Model	KIOLI 37 173
ENCINE	
MODEL	C2S2230C

 Towing Hook 	
 Hydraulic Filter Guard 	
 Rear Work Lights 	

• Front Weight • Rear Hydraulic Valve • Васк Ир Сатега

· Rear Window Wiper

 Front Grille Guard • 3rd Funtion

• LCD Monitor

• Bluetooth Radio

• Beacon Light

• 7 Pin Socket

ТИЗМЯ! СОПІРМЕНТ

asteef my Arm Rests	edsng •
---------------------	---------

• 12V Power Outlet & USB Socket

• Warning / Signal Lamps

• Headlights

• Parking Brake

ngiS VMS •

• PTO Shield • Cruise Control

• 4 Wheel Drive

Joystick Valve

OAVH • Wet Multi Disc Brakes

oTq biM • • Rear PTO

• Rear Differential Lock

• Tilt Steering

Power Steering

• KIOTI Connect Capable

Rear Wheel Weights

• Rear Window Defrost

Front Work Lights

Rear View Mirror

Side View Mirrors

• Sun Visor

Front Wiper

Cup Holder

Fixed Drawbar